

Multiple Conductor Unshielded Plenum Rated



Underwriters
 Laboratories Inc.®
 Listed Type CMP-CL2P C



- Fully color coded 60° C plenum approved PVC insulation.
- 60° C plenum rated PVC jacket.
- Color Code see Table I.
- For use on Class 2 circuits as described in N.E.C. Code as power-limited circuits per Article 725, allow cables rated for use in plenum space without conduit. Consult UL Subject 13 and N.E.C.
- Power-limited circuit cable manufactured to UL Subject 13 for use as outlined in N.E.C. Article 725 - 150 volt maximum.

CATALOG NUMBER	NUMBER OF COND'S	NOMINAL O.D.	WEIGHT LBS/MFT
#20 AWG STRANDED			
1725-20-7-2J	2	.156	13
1725-20-7-3J	3	.165	17
1725-20-7-4J	4	.180	21
1725-20-7-5J	5	.189	26
#18 AWG STRANDED			
1725-18-7-2J	2	.176	18
1725-18-7-3J	3	.186	24
1725-18-7-4J	4	.205	31
1725-18-7-5J	5	.215	37
1725-18-7-6J	6	.232	44
1725-18-7-8J	8	.261	57
1725-18-7-10J	10	.288	70
1725-18-7-12J	12	.311	84

CATALOG NUMBER	NUMBER OF COND'S	NOMINAL O.D.	WEIGHT LBS/MFT
#16 AWG STRANDED			
1725-16-19-2J	2	.196	25
1725-16-19-3J	3	.208	35
1725-16-19-4J	4	.229	45
1725-16-19-6J	6	.260	66
#14 AWG STRANDED			
1725-14-19-2J	2	.222	61
1725-14-19-3J	3	.236	82
1725-14-19-4J	4	.260	105
1725-14-19-6J	6	.297	151



www.avlelec.com